



certified product

### FUNCTIONAL SPECIFICATION

- Actuator controlled socket

### COMMAND MODE

- One hide button with "On-Off" control through Z-wave

### MECHANICAL CHARACTERISTICS

- Dimension: 40x20 mm
- Depth at sight: 40 mm
- Weight: 20 g.

### ELECTRICAL CHARACTERISTICS

- Power supply: 230 VAC 50Hz
- Power consumption: <1 mW
- Maximum load: 10A
- Communication frequency: 868.4MHz
- Maximum communication distance: 20 meters in open field
- Operating temperature: 0-40 ° C
- IP Rating: IP40
- Compatible < Gewiss Chorus
- 

Built in accordance with the Directives:

**B.T.:** 2006/95 / CE

**E.M.C.:** 2004/108 / CE

**R & TTE:** 1999/5 / CE

#### Think Simple s.r.l.

Size, color tone and characteristics of the products shown are only indicative and do not constitute any contractual bond. Think Simple s.r.l. reserves the right to modify its products at any time and without notice in order to better their quality and functionality.

#### HEAD OFFICE

Viale Lino Zanussi, 3  
33170 Pordenone IT  
T +39 0434 516216  
F +39 0434 516230

#### ADMINISTRATIVE OFFICE

Corso Garibaldi, 86  
20121 Milano IT  
T +39 02 65560029  
F +39 02 45498295