

Vitrum One Plus Single Shutter DC


Datasheet

DESCRIPTION

Vitrum One Plus Single Shutter DC is a Z-Wave Plus flush actuator for embedding or junction boxes, to be used in association with satellite buttons.

TECHNICAL AND AESTHETIC SPECIFICATIONS

	A
Power supply	12 - 24 VDC \pm 10%
Rated load current	2 A
Overcurrent protection	5 A
Output circuit power of DC output (resistive load)	48 W (24 VDC)
Power measurement accuracy	+/- 5%
Digital temperature sensor range (sensor must be ordered separately)	-25°C~+80°C (-13~ 176°F), resolution 0.1°C
Operation temperature	-10° ~ +40°C (14 ~ 104°F)
Distance	up to 30 m indoors (98 ft) (depending on building materials)
Dimensions (WxHxD)	41.8 x 36.8 x 15.4 mm / 1,65x1,45x0,66 in
(packaging)	74 x 43 x 86 mm / 2,91x1,69x3,39 in
Weight (including packaging)	21 g (47 g) / 0.74oz (1.66oz)
Electricity consumption	0,4W
For installation in boxes	$\varnothing \geq 60$ mm (2,36 in) or 2M, depth ≥ 60 mm (2,36 in)
Switching	H bridge
Z-Wave Repeater	Yes



	Device	Code (Electronic)	Region	Frequencies
A	Vitrum One Plus Single Shutter DC	900272	EU	868,4 MHz

